



Product Data Sheet

Webro HD Compression BNC Plug IMAGE 360

Description



The Compression HD BNC offer excellent performance and is a quick and easy way to terminate or repair video cables without requiring expert technical know-how. The connectors provide a faster and simpler custom-fit installation suitable for Argosy's Image range of digital video cables.

Suitable for SD, HD & 3G HD-SDI video formats, the one-piece design limits the termination process and chances of losing BNC components. All that is required is the correct compression tool and stripper for the cable type. With a conductor made of tin-coated beryllium copper, they can withstand temperatures between -40 and +70° C.

Product	SKU
WEBRO HD COMPRESSION BNC PLUG IMAGE 360	BA-65-600



Product Data Sheet

Webro HD Compression BNC Plug IMAGE 360

Technical Specification

Webro HD Compression BNC Plug IMAGE 360 Specification

Frequency Range: 0.3 - 3000 MHz	Return Loss(Typical)
Impedance: 75 Ω	0.3 - 500 MHz: -38,1 dB
Amp. Rating (measured): 1,5 A @10°C increase	500 - 860 MHz: -37,7 dB
Shielding Effectiveness: 90 dB @ 30-1000MHz 84 dB @ 1000-3000MHz	860 - 1000 MHz: -37,7 dB
Insulation Resistance: >200 G Ω	1000 - 1750 MHz: -35,8 dB
Dielectric Strength: >2,0 KV	1750 - 2150 MHz: -35,6 dB
Conductor: Tin coated Beryllium copper	2150 - 3000 MHz: -35,6 dB
Dielectric Strength: >2,0 KV	Insertion Loss Max.(Typical)
Temperature	0.3 - 500 MHz: -0,04 dB
Installing: -5° to +50°C	500 - 860 MHz: -0,05 dB
Operating: -40° to +70°C	860 - 1000 MHz: -0,05 dB
Storing: -40° to +70°C	1000 - 1750 MHz: -0,07 dB
	1750 - 2150 MHz: -0,08 dB
	2150 - 3000 MHz: -0,18 dB