



Product Data Sheet

Argosy 1U F Termination Panel

Description



F Termination Panel 1U 1 X 24 | BS-00-9124

Due to manufacturing restrictions this product has an MOQ of 50

Product Data

Frequency Range	0.3 - 3000 MHz
Impedance	75ohms
Amp. Rating	4,5 A @10°C increase
Transfer Impedance	<0,90 m /m @ 5-30MHz
Shielding Effectiveness	>140 dB @ 30-1000MHz
Operating Temperature	-40° to +70° C
Conductor Resistance	5 mΩ
Insulation Resistance	> 200 GΩ
Dielectric Strength	3 KV



Product Data Sheet

Argosy 1U F Termination Panel

Technical Data

Return Loss

0.3 - 500 MHz	-45,0 dB
500 - 860 MHz	-43,0 dB
860 - 1000 MHz	-42,3 dB
1000 - 1750 MHz	-33,5 dB
1750 - 2150 MHz	-31,1 dB
2150 - 3000 MHz	-25,0 dB

Insertion Loss Max.

0.3 - 500 MHz	-0,02 dB
500 - 860 MHz	-0,02 dB
860 - 1000 MHz	-0,02 dB
1000 - 1750 MHz	-0,03 dB
1750 - 2150 MHz	-0,04 dB
2150 - 3000 MHz	-0,05 dB