

Product Data Sheet

Argosy 4K BNC Termination Panels

s or mark holders

Description		
Confraction and the state of th	1U 1X16 4K 2160P BNC	BS-00-3416
CO COSCOLODIO COMO	1U 1X20 4K 2160P BNC	BS-00-3420
	1U 1X24 4K 2160P BNC	BS-00-3424
	2U 1X2O 4K 2160P BNC	BS-00-3520

The Argosy 4K UHD BNC termination panels are design for use in 2160p full HD video circuits.

These panels offer exceptional electrical performance at 12GHz with better than -15.7dB return loss, falling to -26.0dB at 6GHz. These panels are manufactured from extruded Aluminium which delivers a light weight yet extremely strong panel and are fitted with a snap fit Ident strip. They also feature a large OD tie bar with robust end braces, which make landing cables easier and addresses issues associated with smaller bars.

	Product Data	
Impedance	75 Ohm	
Max. Frequency	12GHz	
Dielectric Withstanding	1500 V RMS Max.	
Working Voltage	500V RMS Max	
Temp. Range	- 55 to +85 °C	
RoHS	Yes	
Dielectric	Delrin	
Body	Brass, Nickel Plate	
Contact	Brass, Gold Plate	
Washer	Steel, Nickel Plate	
Locknut	Brass, Nickel Plate	
Durability	500 Cycles per connector	

Argosy 4K BNC



Product Data Sheet

Argosy 4K BNC Termination Panels

