



Product Data Sheet

Argosy 1U ECO Fibre Patch Panel

Description



1U ECO fibre patch panel Loaded with LC connectors to offer an economical, high-density 19" rack mount fibre termination solution. The sliding tray is locked in place with two plastic latches, when fully extended the tray is designed to lower to 45°, or move the tray to the side and it will lock to lower only 10°. This provides the perfect working platform for simple installation or easy maintenance and access even after the panel is installed in the rack.

Available as:

| Product | SKU |
|--|------------|
| ARGOSY 1U ECO 12 WAY SC SIMPLEX OM3 FIBRE TRAY | KT-00-0212 |
| ARGOSY 1U ECO 24 WAY SC SIMPLEX OM3 FIBRE TRAY | KT-00-0224 |
| ARGOSY 1U ECO 12 WAY SC SIMPLEX OS2 FIBRE TRAY | KT-00-0312 |
| ARGOSY 1U ECO 24 WAY SC SIMPLEX OS2 FIBRE TRAY | KT-00-0324 |
| ARGOSY 1U ECO 12 WAY LC DUPLEX OM3 FIBRE TRAY | KT-00-0412 |
| ARGOSY 1U ECO 24 WAY LC DUPLEX OM3 FIBRE TRAY | KT-00-0424 |
| ARGOSY 1U ECO 12 WAY LC DUPLEX OS2 FIBRE TRAY | KT-00-0512 |
| ARGOSY 1U ECO 24 WAY LC DUPLEX OS2 FIBRE TRAY | KT-00-0524 |



Product Data Sheet

Argosy 1U ECO Fibre Patch Panel

Key Benefits

- Panel numbers and rack number identifications labels
- Improved fibre management with recessed adaptors and rear cable entry options
- 45° working angle with no exposed screws or sharp edges
- Screen printed for easy labelling
- Easy style mounting ears, with fixing points for universal front management
- New slot feature allows direct attachment of pre-terminated FastFibre manifold
- Enables gland to be installed with panel in the rack.
- Enables tray to be removed and installed with the panel in the rack

Technical Specification

1U ECO Fibre Patch Panel Specification

| | |
|--|---|
| Height x Width x Depth 1U: 44.4mm x 482mm x 205mm | Cable Entry: 25mm 2 |
| Net Weight: 2.4kg | Easy Slot: 2 |
| Packaged Weight: 3kg | Material Thickness: 1.2mm cold rolled steel |
| Packaged Dimensions: (H) 55mm x (W) 530mm x (D) 260mm | Material Coating: Electrostatic Powder Coating |
| IP Rating: 20 | Colour: Black RAL 9004 |
| Adaptor Type: LC Duplex (48 Fibre) | Operating Temperature: -40°C to +60°C |
| Mounting Adjustment Range: 50mm | Compliant to: This product conforms to the material requirements of RoHS2, REACH/SvHC |
| Cable Entry: 20mm 2 | Designed in accordance with: TIA/EIA 568A.C, ISO/IEC 11801, EN50173, IEC 60304, IEC 61754, EN297-1 |