



Product Data Sheet

PS17 RETROFIT CABLE MARKERS

Description



Retrofit cable idents for cables between 5.8 and 8.5mm in diameter.

Black IDENT NO. 0	LC-00-127
Brown IDENT NO. 1	LC-01-128
Red IDENT NO. 2	LC-02-129
Orange IDENT NO. 3	LC-03-130
Yellow IDENT NO. 4	LC-04-131
Green IDENT NO. 5	LC-05-132
Blue IDENT NO. 6	LC-06-133
Violet IDENT NO. 7	LC-07-134
Grey IDENT NO. 8	LC-08-135
White IDENT NO. 8	LC-09-136

Features

Product Information	
Material	Material
Operating temperatures	-40 to +90°C
Tensile strength at yield	54 N/mm ²
Elongation at break	30 %
Elasticity	2100 N//mm ²
Dielectric strength	28 kV/mm
Flammability	HB UL94



Product Data Sheet

PS17 RETROFIT CABLE MARKERS


Description



Partex PA style markers are a closed, secure type for un-terminated cables. Made from specially designed soft PVC, the spring action bellows allow one marker to cover a variety of cable diameters.

The chevron cut enables easy alignment of multiple characters and excellent legibility is achieved through high quality hot foil marking. Good environmental tolerance makes these markers suitable for most applications.

Colour	No.	PA1/3	(cable size 2.5 50 5.0mm)	PA2/4
Black	0	LA-00-001	LA-00-002	LA-00-013
Brown	1	LA-01-001	LA-01-002	LA-01-013
Red	2	LA-02-001	LA-03-002	LA-02-013
Orange	3	LA-03-001	LA-04-002	LA-03-013
Yellow	4	LA-04-001	LA-04-002	LA-04-013
Green	5	LA-05-001	LA-05-002	LA-05-013
Blue	6	LA-06-001	LA-06-002	LA-06-013
Violet	7	LA-07-001	LA-07-002	LA-07-013
Grey	8	LA-08-001	LA-08-002	LA-08-013
White	9	LA-09-001	LA-09-002	LA-09-013



HEIGHT (H) mm	WIDTH (W) mm	TEXT HEIGHT mm
5.5	4.2	2.6



Product Data Sheet

PS17 RETROFIT CABLE MARKERS

Product Data

Product Data			
	PA1/3 (cable size 2.5 to 5.0mm)	PA2/4 (cable size 4.0 to 10.0mm)	PA3/6 (cable size 8.0 to 16.0mm)
Height (H)	5.5	9.5	16.0mm
Width (W)	4.2	6.6	11.0mm
Text Height	2.6	4.0	4.0
Material		Cadmium-free soft PVC.	
Colours		International resistor colour code or black on white or yellow.	
Print		Hot-foil stamped.	
Temperature		The shape is permanent between 30°C and +70°C.	
Properties		Self-extinguishing, good resistance to chemicals, gamma and UV radiation.	
Legends		0-9, A-Z, +, -, /, earth, or blank.	