



Product Data Sheet

Neutrik NBNC75BJP9 BNC Plug 1505F

Description



The rearTWIST HD BNC cable connector offers a true 75 Ω design and is perfectly suitable for HD applications.

The patented rearTWIST boot guarantees easy access even in high density applications and offers colour coding.

Crimp dimensions: Pin: 1.6 mm (square), Shield: 6.47 mm (hex)

Product	SKU
NEUTRIK NBNC75BJP9 BNC PLUG 1505F	BA-65-5126

Key Benefits

- “rearTWIST Principle” locking/unlocking using the easily accessible soft touch boot (Patent DE 100 48507)
- Ideal for recessed bulkheads where access to the “head” of the connector might be an issue. These connectors turn from the back and not the front
- True 75 Ω design meets the stringent HDTV / DVD requirements
- Leading area: Avoids tilting due to side forces to protect contacts from deformation. Guarantees a lifetime of min. 1000 mating cycles!
- Snug-fit center pin insert provides tactile feedback
- Shield and jacket crimp technology prevents the problem of an exposed grounding braid on cable assemblies
- Excellent cable protection and retention
- Precise Swiss machined brass parts for outstanding durability
- Accessories include colour coded boots in 10 standard colours, crimp tool and dies



Product Data Sheet

Neutrik NBNC75BJP9 BNC Plug 1505F

Technical Specification

Neutrik NBNC75BJP9 BNC Plug 1505F Specification

Connection type: BNC 75 Ω	Contact crimpability: Complies with IEC 60803 and IEC 60352-2
Gender: male	Mechanical
Electrical	Cable O.D.: 6.3 mm
Contact resistance: $\leq 3 \text{ m}\Omega$ (inner)	Cable retention: $> 30 \text{ N}$ (Center)
Contact resistance: $\leq 2 \text{ m}\Omega$ (outer)	Crimp dimensions: 6.47 Hex crimp (shield) 1.6 Square crimp (pin)
Dielectric strength: 1.5 kVdc	Insertion force: $< 25 \text{ N}$
	Lifetime: > 1000 mating cycles
Insulation resistance: $> 5 \text{ G}\Omega$	Locking device: Bayonett
Rated voltage: $< 50 \text{ V}$	Cable anchoring: Jacket crimping
VSWR: $\leq 1.050 / > 32 \text{ dB}$ up to 1 GHz $\leq 1.065 / > 30 \text{ dB}$ up to 2 GHz $\leq 1.100 / > 26 \text{ dB}$ up to 3 GHz	
Environmental	
Temperature range: $-30 \text{ }^\circ\text{C}$ to $+85 \text{ }^\circ\text{C}$	