



# Product Data Sheet

## Lindy HDMI 4 Port Multi-View Switch

### Description



This HDMI 4x1 Multi-View Switch is a high performance video switch which allows signals from four different Full HD sources to be integrated for simultaneous display on a single monitor. Featuring four different viewing modes (Quad-View, Full Screen, Picture and Picture & Dual Video) the Multi-view switch allows for the monitoring of multiple video sources in different viewing configurations to meet the requirements of standard installations.

To ensure optimal performance in mission critical environments the Switch provides seamless switching, ensuring that there is no frame loss whilst switching between the connected source devices or between different picture modes.

Full HD 1080p resolutions are supported on both the input and output for simple integration within typical business environments, whilst the output can be down-scaled to 720p for operation with legacy displays.

Switching between audio and video channels can be completed independently using either the supplied remote control or using the front panel buttons. This independent switching allows a single audio source to be used continuously whilst switching between the connected source devices or conversely a single video source to be monitored whilst the audio source is switched.

This flexible, cost effective switch has been designed to be used in a number of different applications, such as:

- Digital Presentation
- CCTV Surveillance & Control
- Conference & Meeting Room

Please note: HDCP is always enabled on the output connection

Product	SKU
LINDY HDMI 4 PORT MULTI-VIEW SWITCH	LIN-38150



# Product Data Sheet

## Lindy HDMI 4 Port Multi-View Switch

### Key Benefits

- Integrates 4 Full HD 1080p signals for display on a single HDMI display
- Supports 4 viewing modes: Quadview, Picture & Picture, Dual Video and Standard
- Seamless switching between inputs/viewing modes
- Independent switching of audio and video signals
- 2 Year warranty

### Technical Specification

#### Lindy HDMI 4 Port Multi-View Switch Specification

Supports 4 viewing modes: Standard	Connectors: Inputs: 4 x HDMI Type A Female Output: 1 x HDMI Type A Female
Quadview/Multi-Window Display	Seamless Switching: between inputs/viewing modes
Picture and Picture	Audio Pass-through: 2 channel PCM
Dual video	Supports: IR remote control and on-panel control
HDMI 1.3a, HDCP 1.2 and DVI 1.0 Compliant	Power Consumption: 6W
Supports input resolutions up to: 1920x1080p 60Hz 4:4:4 8bit	Operating Temperature: 0°C – 40°C
Output resolution: 1920x1080p 60Hz 4:4:4 8bit or 1280x720p 60Hz 4:4:4 8bit	Storage Temperature: -20°C – 60°C
Supports cable lengths of up to: 15m in/out using 26 AWG cable	Operating Humidity: 20%-90% RH (non-condensing)
Independent switching of: Audio	Storage Humidity: 40%-60% RH