

Product Data Sheet

Lindy DisplayPort to VGA Active Converter





The Lindy DisplayPort 1.2 to VGA Converter is ideal for connecting a DisplayPort equipped source such as a PC or laptop to a VGA monitor. It supports high definition video resolutions up to 1920x1080@60Hz. Active conversion ensures compatibility with various graphics cards including AMD Eyefinity, NVIDIA surround and Intel Collage.

The converter can also be used to add another display to extend the available desktop workspace and increase productivity. Internal copper shielding provides enhanced reliability and compatibility. The converter is also ideally suited for travelling due to its compact, lightweight form factor and convenient Plug & Play installation.

| Product | SKU |
|---|-----------|
| LINDY DISPLAYPORT TO VGA ACTIVE CONVERTER | LIN-41006 |

Key Benefits

- Converts a DisplayPort signal into VGA
- Supports resolutions up to 1920x1080@60Hz

All products and companies referred to herein are trade


· Add a VGA monitor as a secondary display

Quick and simple Plug & Play installation

narks or registered trademarks of their respective companies or mark holders

• 2 year warranty

+44 1844 202101 1 sales@argosycable.com 1





Product Data Sheet

Lindy DisplayPort to VGA Active Converter

| Technical Specification | | |
|---|---|--|
| Lindy DisplayPort to VGA Active Converter Specification | | |
| Specifications | Housing Material: TPE | |
| AV Interface: DisplayPort to VGA | Jacket Material: PVC | |
| Interface Standard: DisplayPort 1.2, VGA | Jacket Diameter: 6.5mm (0.26in) | |
| Supported Bandwidth: 10.8Gbps | Minimum Bend Radius: 70mm (2.76in) | |
| Maximum Input Resolution: 1920x1080@60Hz | Net Weight: 0.045kg (0.1lb) | |
| Maximum Output Resolution: 1920x1080@60Hz | Operating Temperature: -20°C - 80°C (-4°F - 176°F) | |
| Chipset: ANX9833 | Storage Temperature: -20°C - 70°C (-4°F - 158°F) | |
| HDCP Support: - | Humidity: 20 - 90% RH (non-condensing) | |
| Supported Audio: - | Colour: Black | |
| Separate Audio Ports: - | Miscellaneous | |
| Special Features: - | Packaging Type: Polybag | |
| Connectors | Packaging Dimensions: 160x160x20mm (6.3x6.3x0.79in) | |
| Input: DisplayPort Male | Gross Weight: 0.049kg (0.011lb) | |
| Output: VGA Female | Warranty (Years): 2 | |
| Physical Properties | Certified: CE, UKCA, FCC, RoHS & REACH | |
| Dimensions (approx.) WxDxH: 38x61x17mm (1.5x2.4x0.67in) 20x36x11mm (0.79x1.42x0.43in)/DP | Package Contents | |
| Cable Length: 150mm (5.91in) | DisplayPort 1.2 to VGA Active Converter | |

sales@argosycable.com +44 1844 202101 argosycable.com arks or registered trademarks of their respective companies or mark holders