



# Product Data Sheet

Lindy HDMI to DVI Cable, Black Line

## Description



From the Lines cable connectivity concept developed by Lindy, Black Line HDMI to DVI-D cables are fully featured, entry level connection solutions, perfect for connecting PCs to monitors or projectors.

Black Line HDMI to DVI-D cables feature triple shielded construction with 30AWG tinned copper conductors for performance and corrosion resistance. Nickel connectors and 24K gold plated contacts maintain signal integrity and reliability.

The tough PVC housing incorporates an integrated finger grip for easy installation. Large thumb screws allow the connector to be tightened into place without the need for a screwdriver and a flexible strain relief prolongs cable life.

Black Line HDMI to DVI-D cables support resolutions up to 1920x1200@60Hz including HDTV resolutions up to 1080p.

Product	SKU
LINDY HDMI TO DVI CABLE, BLACK LINE	LIN-36272

## Key Benefits

- Entry level HDMI Male to DVI-D Male cable for home and small office applications
- Supports DVI resolutions up to 1920x1200@60Hz and HDTV resolutions up to 1080p
- Robust PVC housing, nickel connectors, 24K gold plated contacts
- Triple shielded cable, corrosion resistant tinned copper 30AWG conductors
- 10 year warranty



# Product Data Sheet

Lindy HDMI to DVI Cable, Black Line

## Technical Specification

### Lindy HDMI to DVI Cable, Black Line Specification

<b>Connectors</b>	<b>Jacket Material:</b> PVC
<b>Connector A:</b> HDMI Type A Male	<b>Conductor Material:</b> Tinned Copper
<b>Connector B:</b> DVI-D Male (Single Link)	<b>Conductor Gauge:</b> 30AWG
<b>Housing Material:</b> PVC	<b>Shielding:</b> Aluminium/Magnesium Braid 85%
<b>Connector Plating:</b> Nickel	<b>Specifications</b>
<b>Pin Construction:</b> Brass	<b>Supported Bandwidth:</b> 4.95Gbps
<b>Pin Plating:</b> 24K Gold 1µm	<b>Maximum Resolution:</b> 1920x1200@60Hz
<b>Dimensions, HDMI Connector (approx.) WxDxH:</b> 21.4x34.2x12.7mm (0.84x1.35x0.5in)	<b>Nominal Attenuation:</b> 1 – 825Mhz < 12db
<b>Dimensions, DVI Connector (approx.) WxDxH:</b> 36.8x44.5x12.5mm (1.45x1.75x0.49in)	<b>Minimum Bend Radius:</b> 55mm (2.17in)
<b>Cable Construction</b>	<b>Operating Temperature:</b> -20°C - 80°C (-4°F - 176°F)
<b>Length:</b> 2m (6.56ft)	<b>Storage Temperature:</b> -25°C - 85°C (-13°F - 185°F)
<b>Standard:</b> DVI-D Single Link	<b>Miscellaneous</b>
<b>Colour:</b> Black	<b>Packaging Type:</b> Polybag
<b>Type:</b> Round	<b>Warranty (Years):</b> 10
<b>Jacket Diameter:</b> 5.5mm (0.22in)	<b>Certified:</b> RoHS, REACH, UL