



Product Data Sheet

Lindy High Speed HDMI Cable, Black Line

Description



From the lines cable connectivity concept developed by Lindy, Black Line High Speed HDMI cables are fully featured, entry level high resolution connection solutions, perfect for home and small office use.

Black Line High Speed HDMI cables feature triple shielded construction with 30AWG copper coated steel conductors for premium performance and corrosion resistance. Nickel connectors and gold flashed contacts maintain signal integrity and reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 8bit are supported. Black Line HDMI cables are also capable of transmitting 32 channel audio and Dolby® True HD.

The HDMI 2.0 specification is supported for 18Gbps bandwidth capacity in cable lengths up to 15m.

Black Line HDMI cables are available in lengths from 0.5m to 15m.

Product	SKU
LINDY HIGH SPEED HDMI CABLE, BLACK LINE	FK-00-80005

Key Benefits

- Entry level High Speed HDMI 2.0 cable for home and small office applications
- Supports UHD resolutions up to 4096x2160@60Hz 4:4:4 8bit
- Robust PVC housing, nickel connectors, gold flashed contacts
- Triple shielded cable, corrosion resistant copper coated steel 30AWG conductors
- HDMI 2.0 compliant: 3D, 4K, 18Gbps, HEC, ARC, CEC, Dolby® True HD, DTS-HD Master Audio; 10 year warranty



Product Data Sheet

Lindy High Speed HDMI Cable, Black Line

Technical Specification

Lindy High Speed HDMI Cable, Black Line Specification

Connectors	Conductor Material: Copper Coated Steel
Connector A: HDMI Type A Male	Conductor Gauge: 30AWG
Connector B: HDMI Type A Male	Shielding: Foil
Housing Material: PVC	Specifications
Connector Plating: Nickel	Supported Bandwidth: 18Gbps
Pin Construction: Phosphor Bronze	Maximum Resolution: 4096x2160@60Hz 4:4:4 8bit
Pin Plating: Gold Flash	Nominal Attenuation: 300kHz-825MHz <5dB, 825MHz-2.475GHz <5dB, 2.475GHz-4.125GHz <12dB, 4.125GHz-5.1GHz <20dB
Dimensions, HDMI Connector (approx.) WxDxH: 19.2x34.1x10.6mm (0.76x1.34x0.42in)	Minimum Bend Radius: 60mm (2.36in)
Cable Construction	Operating Temperature: -10°C - 80°C (14°F - 176°F)
Length: 0.5m (1.64ft) 6470 - 0.5m (1.64ft), 1m (3.28ft), 2m (6.56ft), 3m (9.84ft), 5m (16.44ft), 7.5m (24.60ft), 10m (32.80ft), 15m (49.21ft)	Storage Temperature: -10°C - 80°C (14°F - 176°F)
Standard: High Speed HDMI with Ethernet	ATC Approved: No
Colour: Black	Miscellaneous
Type: Round	Packaging Type: Polybag
Jacket Diameter: 6mm (0.24in)	Warranty (Years): 10
Jacket Material: PVC	Certified: RoHS, REACH, UL