



Product Data Sheet

Lindy DisplayPort 1.4 Cable, Anthra Line

Description



From the Lines cable connectivity concept developed by Lindy, Anthra Line DisplayPort cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line DisplayPort cables are premium connections that feature triple shielded with 28AWG tinned copper conductors for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit, including 4K 4096x2160@144Hz 4:2:2 10bit and HDCP are supported. DisplayPort 1.4 technology and DisplayPort compliance certification ensures compatibility with all DisplayPort enabled devices.

Anthra Line DisplayPort cables are available in lengths from 0.5m to 5m.

Black Line HDMI to DVI-D cables are available in lengths of 0.5m to 10m.

Product	SKU
LINDY DISPLAYPORT 1.4 CABLE ANTHRA LINE	FK-00-05005

Key Benefits

- Professional choice DisplayPort 1.4 cable for commercial and high performance AV and IT installations
- Supports UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit including 4K 4096x2160@144Hz 4:2:2 10bit
- Robust ABS housing 24K gold plated connectors and contacts
- Triple shielded cable, corrosion resistant tinned copper 28AWG conductors
- DisplayPort 1.4, 32.4Gbps; 10 year warranty



Product Data Sheet

Lindy DisplayPort 1.4 Cable, Anthra Line

Technical Specification

Lindy DisplayPort 1.4 Cable, Anthra Line Specification

Connectors	Conductor Material: Tinned Copper
Connector A: DisplayPort Male	Conductor Gauge: 28AWG
Connector B: DisplayPort Male	Shielding: Copper Braid 65%
Housing Material: ABS	Specifications
Connector Plating: 24K Gold 15µm	Supported Bandwidth: 32.4Gbit/s
Pin Construction: Phosphor Bronze	Maximum Resolution: 7680x4320@60Hz 4:2:2 8bit 4096x2160@144Hz 4:2:2 10bit
Pin Plating: 24K Gold 3µm	Nominal Attenuation: 100MHz-450MHz <5.1dB, 450MHz-8100MHz <33.28dB
Dimensions(approx.) WxDxH: 21.0x38.9x13.6mm (0.83x1.53x0.54in)	Minimum Bend Radius: 58.4mm (2.14in)
Cable Construction	Operating Temperature: -20°C - 80°C (-4°F - 176°F)
Length: 0.5m (1.64ft), 36481 - 1m (3.28ft), 36482 - 2m (6.56ft), 36483 - 3m (9.84ft), 36484 - 5m (16.40ft)	Storage Temperature: -25°C - 85°C (-13°F - 185°F)
Standard: DisplayPort 1.4	ATC Approved
Colour: Black	Miscellaneous
Type: Round	Packaging Type: Polybag
Jacket Diameter: 7.3mm (0.29in)	Warranty (Years): 10
Jacket Material: PVC	Certified: RoHS, REACH, UL