



# Product Data Sheet

## Lindy DVI-D Dual Link Cable, Gold Line

### Description



From the Lines cable connectivity concept by Lindy, Gold Line DVI-D Dual Link cables are the no compromise, high resolution connection solution for use in the most demanding professional environments.

Gold Line DVI-D Dual Link cables feature triple shielded construction with 28AWG OFC conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

The full metal housing incorporates an integrated finger grip for easy installation. Large thumb screws allow the connector to be tightened into place without the need for a screwdriver and a flexible strain relief prolongs cable life.

These superior quality cables utilise a unique low attenuation design that ensures consistent and reliable transmission even over very long distances.

Gold Line DVI-D Dual Link cables support DVI resolutions up to 2560x1600@60Hz including HD resolutions up to 1080p.

Gold DVI-D Dual Link cables are available in lengths from 0.5m to 25m.Connectors.

Product	SKU
LINDY DVI-D DUAL LINK CABLE, GOLD LINE	LIN-36202

### Key Benefits

- No compromise DVI-D Dual Link cable for demanding environments and mission critical systems
- Supports DVI resolutions up to 2560x1600@60Hz and HD resolutions up to 1080p
- Full metal 24K gold plated housing, 24K gold plated connectors and contacts
- Low attenuation triple shielded cable, corrosion resistant, high performance OFC 28AWG conductors
- 25 year warranty



# Product Data Sheet

## Lindy DVI-D Dual Link Cable, Gold Line

### Technical Specification

#### Lindy DVI-D Dual Link Cable, Gold Line Specification

<b>Connectors</b>	<b>Conductor Material:</b> OFC Copper
<b>Connector A:</b> DVI-D Male (Dual Link)	<b>Conductor Gauge:</b> 28AWG
<b>Connector B:</b> DVI-D Male (Dual Link)	<b>Shielding:</b> Copper Braid 85%
<b>Housing Material:</b> 24K Gold Plated Metal	<b>Specifications</b>
<b>Connector Plating:</b> 24K Gold 3µm	<b>Supported Bandwidth:</b> 9.9 Gbps
<b>Pin Construction:</b> Phosphor Bronze	<b>Maximum Resolution:</b> 2560x1600@60Hz
<b>Pin Plating:</b> 24K Gold 15µm	<b>Nominal Attenuation:</b> 1 - 825Mhz < 8db
<b>Dimensionsn(approx.) WxDxH:</b> 39.5x16.5x44.5mm (1.55x0.65x1.73in)	<b>Minimum Bend Radius:</b> 120mm (4.72in)
<b>Cable Construction</b>	<b>Operating Temperature:</b> -20°C - 80°C (-4°F - 176°F)
<b>Available in lengths:</b> 0.5m to 25m	<b>Storage Temperature:</b> -25°C - 85°C (-13°F - 185°F)
<b>Standard:</b> DVI-D Dual Link	<b>Miscellaneous</b>
<b>Colour:</b> Grey	<b>Packaging Type:</b> Polybag
<b>Type:</b> Round	<b>Warranty (Years):</b> 25
<b>Jacket Diameter:</b> 8.6mm (0.34in)	<b>Certified:</b> RoHS, REACH, UL
<b>Jacket Material:</b> PVC	