

Product Data Sheet

Lindy USB 2.0 Type A to B Cable, Anthra Line



From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type A to B cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

Anthra Line USB 2.0 Type A to B cables are available in lengths from 0.2m to 10m.

Product	SKU
LINDY USB 2.0 TYPE A TO B CABLE, ANTHRA LINE	RB-00-9301

Key Benefits

- Professional choice USB 2.0 Type A to B cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 480Mbps
- Robust PVC housing, nickel connectors and gold plated contacts
- Double shielded cable, corrosion resistant tinned copper conductors

argosycable.com

USB 2.0, 480Mbps; 10 year warranty

+44 1844 202101 sales@argosycable.com

All products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders



Product Data Sheet Lindy USB 2.0 Type A to B Cable, Anthra Line

Lindy USB 2.0 Type A-B Cable, Anthra Line Specification	
Connector A: USB 2.0 Type A Male	Conductor Material: Tinned Copper
Connector B: USB 2.0 Type B Male	Conductor Gauge: 26/28AWG
Housing Material: PVC	Shielding: Aluminium Magnesium Braid
Connector Plating: Nickel	Specifications
Pin Construction: Copper	Supported Bandwidth: 480Mbps
Pin Plating: 24K Gold	Maximum Resolution: -
Dimensionsn USB A (approx.) WxDxH: 15.5x35x7.8mm (0.61x1.38x0.31in)	Nominal Attenuation: 5.8db/km
Dimensionsn USB B (approx.) WxDxH: 11.8x35x10.2mm (0.47x1.38x0.40in)	Minimum Bend Radius: 16mm (0.63in)
Cable Construction	Operating Temperature: 0°C - 60°C (32°F - 140°F)
Length: 0.2m, 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m	Storage Temperature: 0°C - 60°C (32°F - 140°F)
Standard: USB 2.0	Miscellaneous
Colour: Black	Packaging Type: Polybag
Type: Round	Warranty (Years): 10
Jacket Diameter: 4.4mm (0.17in)	Certified: RoHS, REACH, UL

arks or registered trad

All products and companies refe