



Product Data Sheet

Lindy USB 2.0 Type A to B Cable, Cromo Line

Description



From the Lines cable connectivity concept developed by Lindy, Cromo Line USB 2.0 Type A to B cables are high performance, designer connections that combine premium construction with striking connector architecture.

Cromo Line USB 2.0 cables feature double shielded construction with tinned copper conductors for premium performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

Cromo Line USB 2.0 Type A to B cables are available in lengths of 0.5m to 7.5m.

| Product | SKU |
|---|------------|
| LINDY USB 2.0 TYPE A TO B CABLE, CROMO LINE | RB-08-8102 |

Key Benefits

- Superior performance and design USB 2.0 Type A to B cable
- Supports data transfer speeds up to 480Mbps
- Chrome design ABS housing, gold plated connectors and contacts
- Double shielded cable, corrosion resistant, high performance tinned copper conductors
- USB 2.0, 480Mbps; 10 year warranty



Product Data Sheet

Lindy USB 2.0 Type A to B Cable, Cromo Line

Technical Specification

Lindy USB 2.0 Type A- B Cable, Cromo Line Specification

| | |
|---|---|
| Connectors | Jacket Material: PVC |
| Connector A: USB 2.0 Type A Male | Conductor Material: Tinned Copper |
| Connector B: USB 2.0 Type B Male | Conductor Gauge: 24/28AWG |
| Housing Material: Chrome Plated, ABS | Shielding: Copper Braid 85% |
| Connector Plating: Gold 1µm | Specifications |
| Pin Construction: Phosphor Bronze | Supported Bandwidth: 480Mbps |
| Pin Plating: Gold 3µm | Maximum Resolution: - |
| Dimensions USB A (approx.) WxDxH: 16x35x8.3mm (0.63x1.38x0.34in) | Nominal Attenuation: 0.5-5m: 0.5-400MHz < 5.8db, 7.5m: 0.5-400MHz < 7.0db |
| Dimensions USB B (approx.) WxDxH: 11.8x35x10.2mm (0.47x1.38x0.40in) | Minimum Bend Radius: 55mm (2.2in) |
| Cable Construction | Operating Temperature: -20°C - 80°C (-4°F - 176°F) |
| Length: 0.5m, 1m, 2m, 3m, 5m, 7.5m | Storage Temperature: -25°C - 85°C (-13°F - 185°F) |
| Standard: USB 2.0 | Miscellaneous |
| Colour: Grey | Packaging Type: Polybag |
| Type: Round | Warranty (Years): 10 |
| Jacket Diameter: 4.6mm (0.18in) | Certified: RoHS, REACH, UL |