

# Product Data Sheet

Lindy USB 2.0 Type A Extension Cable, Anthra Line, Grey



From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type A Extension, grey, cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with copper conductors for performance and corrosion resistance. High quality gold plated contacts and nickel connectors maintain optimal signal integrity and maximum reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

This product features a grey finish effect on the cable.

Anthra Line USB 2.0 Type A Extension cables are available in lengths from 0.2m to 5m.

Product	SKU
LINDY USB 2.0 TYPE A EXTENSION CABLE, ANTHRA LINE, GREY	RB-08-9802

### Key Benefits

- Professional choice USB 2.0 Type A Extension cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 480Mbps
- Robust PVC housing, nickel connectors and gold plated contacts

All products and companies referred to he

• Double shielded cable, corrosion resistant tinned copper conductors

argosycable.com

• USB 2.0, 480Mbps; 10 year warranty

narks or registered trademarks of their respective companies or mark holders

#### +44 1844 202101 I sales@argosycable.com



# Product Data Sheet

Lindy USB 2.0 Type A Extension Cable, Anthra Line, Grey

### **Technical Specification**

Connectors	Jacket Material: PVC
Connector A: USB 2.0 Type A Male	Conductor Material: Tinned Copper
Connector B: USB 2.0 Type A Female	Conductor Gauge: 26/28AWG
Housing Material: PVC	Shielding: Aluminium Magnesium Braid
Connector Plating: Nickel	Specifications
Pin Construction: Copper	Supported Bandwidth: 480Mbps
Pin Plating: 24K Gold	Maximum Resolution: -
Dimensions USB A Male (approx.) WxDxH: 15.5x35x7.8mm (0.61x1.38x0.31in)	Nominal Attenuation: 5.8db/km
<b>Dimensions USB A Female (approx.) WxDxH:</b> 17x35x9.8mm (0.67x1.38x0.39in)	Minimum Bend Radius: 16mm (0.63in)
Cable Construction	<b>Operating Temperature:</b> 0°C - 60°C (32°F - 140°F)
<b>Length:</b> 0.2m, 0.5m, 1m, 2m, 3m, 5m	<b>Storage Temperature:</b> 0°C - 60°C (32°F - 140°F)
Standard: USB 2.0	Miscellaneous
Colour: Grey	Packaging Type: Polybag
Type: Round	Warranty (Years): 10
Jacket Diameter: 4.4mm (0.17in)	Certified: RoHS, REACH, UL