



Product Data Sheet

Lindy USB 3.2 Type A to B Cable, 5Gbps, Anthra Line

Description



The Anthra Line USB 3.2 Type A to B cables from Lindy's Cable Lines concept are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 3.2 cables are premium connections that feature triple shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

USB bandwidths up to 5Gbps are supported for rapid transfer of large data volumes.

Anthra Line USB 3.2 Type A to B cables are available in the following lengths: 0.5m, 1m, 2m, 3m and 5m.

Information about USB generations

We have adapted the naming of our USB 3 cables to follow the updated USB specification.

USB 3.0 and USB 3.1 Gen 1 have been renamed to USB 3.2 Gen 1, supporting data transfer up to 5Gbps

USB 3.1 and USB 3.1 Gen 2 are now called USB 3.2 Gen 2, supporting data transfer rates up to 10 Gbps

USB 3.2 Gen 2x2 is a new standard, supporting data transfer rates up to 20 Gbps

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

Product	SKU
LINDY USB 3.2 TYPE A TO B CABLE, 5GBPS, ANTHRA LINE	RB-00-94005



Product Data Sheet

Lindy USB 3.2 Type A to B Cable, 5Gbps, Anthra Line

Key Benefits

- Professional choice USB 3.2 Gen 1 Type A to B cable for commercial and high performance AV and IT installations
- SuperSpeed USB - supports data transfer speeds up to 5Gbps (USB 3.0, USB 3.1 Gen 1)
- Robust PVC housing, gold plated connectors and contacts
- Triple shielded cable, corrosion resistant tinned copper conductors
- 10 year warranty

Technical Specification

Lindy USB 3.2 Type A-B, 5Gbps, Anthra Line Specification

Connectors	Jacket Material: PVC
Connector A: USB 3.2 Type A Male	Conductor Material: Tinned Copper
Connector B: USB 3.2 Type B Male	Conductor Gauge: Power: 24AWG Data: 28AWG
Housing Material: PVC	Shielding: Aluminium Braid 85%
Connector Plating: Gold Plated	Specifications
Pin Construction: Cooper	Supported Bandwidth: 5Gbps
Pin Plating: Gold Plated	Maximum Resolution: -
Dimensions USB A (approx.) WxDxH: 15.5x35x7.8mm (0.61x1.38x0.31in)	Nominal Attenuation: 0.5-5m: 0.5MHz-7.5GHz
Dimensions USB Micro-B (approx.) WxDxH: 12.2x35x13.5mm (0.48x1.38x0.53in)	Minimum Bend Radius: 48mm (1.89in)
Cable Construction	Operating Temperature: 0°C - 60°C (32°F - 140°F)
Length: 0.5m, 1m, 2m, 3m, 5m	Storage Temperature: 0°C - 60°C (32°F - 140°F)
Standard: USB 3.2 Gen 1	Miscellaneous
Colour: Black	Packaging Type: Polybag
Type: Round	Warranty (Years): 10
Jacket Diameter: 5.5mm (0.22in)	Certified: RoHS, REACH, UL