



Product Data Sheet

Lindy 50m Cat.6 HDMI & USB KVM Extender

Description



* Please Note: The preset EDID of the extender is 1920x1080p, other resolutions including 1920x1200p are available via the EDID cloning function described in the user manual.

This KVM Extender allows you to control your PC using a keyboard, mouse and monitor with a maximum resolution of Full HD 1080p or 1920x1200* at distances of up to 50m (150 feet) using inexpensive CAT6 cable (not included). It supports HDMI signals including 3D, 1080p24 Blu-ray, audio and HDCP.

The KVM Extender Classic consists of a transmitter unit which is installed near the computer and a receiver unit installed near the user console. The Receiver unit connects to a USB keyboard and mouse, HDMI monitor and offers a Stereo audio port via 3.5mm connector.

The Transmitter unit offers the same connections and in addition, an optional local console port (bypass).

Product	SKU
LINDY 50M CAT.6 HDMI & USB KVM EXTENDER	LIN-39371

Key Benefits

- Provides a convenient real-time method of remotely controlling a PC
- Extends high resolution video up to Full HD 1080p / 1920x1200* up to 50m
- Supports USB keyboard and mouse signals - no other USB devices are supported
- Easy, user friendly installation - no software required
- 2 year warranty



Product Data Sheet

Lindy 50m Cat.6 HDMI & USB KVM Extender

Technical Specification

Lindy 50m C6 HDMI & USB KVM Extender Specification	
Specifications	Power: 5.5/2.5mm DC socket
AV Interface: HDMI	Physical Properties
Interface Standard: USB	Dimensions WxDxH: 115x60x28mm (4.53x2.36x1.1in)
Interfaces Standard: HDMI 1.4, USB (HID)	Housing Material: Metal
Supported Bandwidth: 4.95 Gbps	Net Weight: 0.32kg (0.71lb) per unit
Maximum Distance: 50m (164.04ft)	Operating Temperature: 0°C - 60°C (32°F - 140°F)
Maximum Resolution: 1920x1080@60Hz	Storage Temperature: -20°C - 70°C (-4°F - 158°F)
HDCP Support: 1.4	Humidity: 0 - 90% RH (non-condensing)
Supported Audio: Analog Stereo	Power Requirements: 5VDC 1.2A
Separate Audio Ports: 1 x 3.5mm (Female)	Colour: Black
Transmission Protocol: -	Miscellaneous
Transmission Medium: 1 x Cat.6 cable	Packaging Type: Carton box
Laser Class (only for Fibre): -	Packaging Dimensions: 260x170x65mm (10.24x6.69x2.56in)
Wavelength (only for Fibre): -	Gross Weight: 1.4kg (3.09lb)
Special Features: -	Warranty: 2
Connectors	Certified: CE, UKCA, FCC, RoHS & REACH
Transmitter KVM Interfaces: 2 x HDMI (Female), 2 x USB Type A (Female), USB Type B (Female), 2 x 3.5mm (Female)	Package Content
Transmitter Extension Port: RJ45 (Female)	Transmitter and Receiver
Receiver Console Interface: HDMI (Female), 2 x USB Type A (Female), 3.5mm (Female)	USB 2.0 A/B cable (approx. 1.8m (5.91ft) – for Transmitter)
Receiver Extension Port: RJ45 (Female)	2 x Multi-Country Power Supply (EU, UK, US, AUS)
Bidirectional Ports: -	LINDY Manual
Other Interfaces: -	