



Product Data Sheet

Lindy 10m USB 3.0 Active Cable

Description



The Lindy USB 3.0 Active Cable uses built-in active electronics to extend the cable length of a USB 3.0 device by an additional 10m whilst continuing to support data transfer rates of up to 5Gbps.

With USB A male and USB B male connectors this product allows Type B devices such as printers to be connected directly at longer distances and ensures flexible positioning.

The Lindy USB 3.0 Active Extension Cable is compatible with all USB Type A equipped computers. With plug and play functionality, this extension cable can be installed quickly and with minimum fuss.

It is recommended that this extender is used with low power or self powered USB peripherals and not high power consuming devices, unless they have their own power supply.

Information about USB 3.0, 3.1 & 3.2

- USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.
- USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.
- USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Product	SKU
LINDY 10M USB 3.0 ACTIVE CABLE	LIN-43098



Product Data Sheet

Lindy 10m USB 3.0 Active Cable

Key Benefits

- 10 metre USB 3.0 Active Repeater Cable
- Supports transfer rates up to 5Gbps
- Plug & Play installation
- Ideal for direct device connection
- 2 year warranty

Technical Specification

Lindy 10m USB 3.0 Active Cable Specification

Connectors	Jacket Diameter: 7mm +/- 0.15mm (0.28in +/- 0.01in)
Connector A: USB Type A Male	Jacket Material: PVC
Connector B: USB Type A Male	Conductor Material: Copper
Power: -	Conductor Gauge: 28/28/22AWG
Housing Material: Plastic	Shielding: 85% Aluminium
Connector Plating: Nickel	Specifications
Pin Construction: Copper	Supported Bandwidth: 5 Gbps
Pin Plating: Nickel	Nominal Attenuation: 100 MHz, -1.5 dB
Dimensions (approx.) WxDxH:	1.25 GHz, -5.0 dB
USB A Male: 16x49x9mm (0.63x3.7x0.35in)	2.5 GHz, -7.5 dB
USB A Male: 10x52x13mm (0.39x2.05x0.51in)	7.5 GHz, -25 dB
Repeater (2x): 35x100x15mm (1.26x3.94x0.59in)	Minimum Bend Radius: 60mm (2.36in)
Cable Construction	Maximum Tensile Load: -
Length: 10m (32.81ft)	Operating Temperature: 0°C - 55°C (32°F - 131°F)
Standard: USB 3.1 Gen 1 / 3.0	Storage Temperature: -20°C - 85°C (-4°F - 185°F)
Colour: Black	Transmission Medium: Twisted Pair
Type: Round	Transmission Technology: USB 3.0



Product Data Sheet

Lindy 10m USB 3.0 Active Cable

Technical Specification

Lindy 10m USB 3.0 Active Cable Specification

Miscellaneous	Warranty (Years): 2
Packaging Type: Polybag	Certified: CE, UKCA, FCC, RoHS & REACH
Packaging Dimensions: 300x300x80mm (11.81x11.81x3.15in)	Package Contents
Net Weight: 0.5 (1.1lb)	USB 3.0 Active Cable 10m
Gross Weight: 0.530kg (1.17lb)	Lindy Manual