



Product Data Sheet

Lindy 7 Port USB 3.0 Metal Hub

Description



The Lindy 7 Port USB 3.0 Metal Hub has been designed to provide reliable performance in demanding operational environments.

This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for use in industrial environments.

Backwards compatibility with USB 2.0/1.1/1.0 means the hub can simultaneously support older USB peripherals or systems that lack USB 3.0 capabilities, extending their lifetime and giving a greater return on investment.

Each port features individual short circuit protection, while the included power supply ensures secure and uninterrupted electricity supply.

Information about USB 3.0, 3.1 & 3.2

- USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.
- USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.
- USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Product	SKU
LINDY 7 PORT USB 3.0 METAL HUB	LIN-43128

Key Benefits

- Provides 7 USB 3.0 SuperSpeed ports with data rates up to 5Gbps
- Hard-wearing USB Hub - Perfect for industrial applications
- Robust metal housing with high EMC protection and integrated brackets for mounting
- USB bus-powered, or can be externally powered
- 2 year warranty



Product Data Sheet

Lindy 7 Port USB 3.0 Metal Hub

Technical Specification

Lindy 7 Port USB 3.0 Metal Hub Specification

Specifications	Operating Temperature: 0°C - 50°C (32°F -122°F)
USB Standard: USB 3.1 Gen 1 / 3.0	Storage Temperature: -20°C - 60°C (-4°F -140°F)
Supported Bandwidth: 5 Gbps	Humidity: 90% RH (non-condensing)
Chipset: 2 x VL811	Power Requirements: 16VDC 2A
Compatibility: USB Type A equipped computers	Colour: Black
Power Delivery: -	Miscellaneous
Special Features: Integrated brackets for mounting	Packaging Type: Carton Box
Connectors	Packaging Dimensions: 260x180x70mm (10.24x7.09x2.76in)
Input: 1 x USB Type B (Female)	Gross Weight: 0.8kg (1.76lb)
Output: 7 x USB Type A (Female)	Warranty (Years): 2
Power: DC screw connector	Certified: CE, UKCA, FCC, RoHS, REACH & California Proposition 65
Physical Properties	Package Contents
Dimensions WxDxH: 185x75x20mm (7.28x2.95x0.79in)	7 Port USB 3.0 Metal Hub
(Fixed) Cable Length: -	0.8m USB 3.0 Type A to B Cable
Housing Material: Metal	Multi-Country Power Supply (EU, UK, US & AU) with screw type DC connector
Net Weight: 0.379kg (0.84lb)	