



Product Data Sheet

Lindy Cat.6 U/UTP Network Cable, Black

Description



Cat.6 U/UTP PVC network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250MHz. The unshielded version (U/UTP) can be used for Gigabit Ethernet thanks to the special design of the electrophysical parameters (NEXt, FEXt, etc.) despite the lack of shielding. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Product	SKU
LINDY CAT.6 U/UTP NETWORK CABLE, BLACK	FJ-00-6801

Key Benefits

- Twisted Pair Patch Cable with RJ45 connectors
- Cat.6 U/UTP, PVC
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 10 year warranty



Product Data Sheet

Lindy Cat.6 U/UTP Network Cable, Black

Technical Specification

Lindy Cat.6 U/UTP Network Cable, Black Specification

Connectors	Conductor Material: Copper
Connector A: RJ45 Male	Conductor Gauge: 24AWG
Connector B: RJ45 Male	Shielding: -
Housing Material: Polycarbonate	Specifications
Connector Plating: -	Supported Bandwidth: 250MHz
Pin Construction: Copper Alloy	Nominal Attenuation: 32.8dB/100m @250MHz
Pin Plating: Gold plated	Minimum Bend Radius: 69mm (2.72in)
Dimensions (approx.) WxDxH: 11.6x22.8x8.3mm (0.46x0.90x0.33in)	Operating Temperature: -10°C - 60°C (14°F - 140°F)
Cable Construction	Storage Temperature: -20°C - 75°C (-4°F - 167°F)
Length: 0.3m, 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m	Miscellaneous
Colour: Black	Packaging Type: Polybag
Type: Cat.6	Warranty (Years): 10
Jacket Diameter: 5.8mm (0.23in)	Certified: RoHS, REACH, UL, California Proposition 65
Jacket Material: PVC	