



Product Data Sheet

Lindy 3 Port TosLink (Optical) Digital Audio Splitter

Description



The Lindy 3 Port TosLink (Optical) Digital Audio Splitter allows the connection of up to 3 digital optical (SPDIF, TosLink) output devices such as; speakers, amplifiers or soundbars to a single digital audio source device.

Support for sampling rates up to 96kHz and audio and compatibility with multi-channel Dolby Digital & DTS audio formats ensures a reliable, loss-less audio transmission.

A compact, minimalistic design and low power requirement through USB ensures maximum flexibility within AV installations, ideal for smaller home AV configurations and larger office, education or retail applications.

| Product | SKU |
|---|-----------|
| LINDY 3 PORT TOSLINK (OPTICAL) DIGITAL AUDIO SPLITTER | LIN-70445 |

Key Benefits

- Sends a single digital audio signal to up to 3 output devices
- Supports 2-channel LPCM, DTS & Dolby Digital audio
- Transmits digital audio signals up to 40m without degradation using high quality optical audio cables
- Minimalistic, compact design allows for discreet installation
- 2 year warranty



Product Data Sheet

Lindy 3 Port TosLink (Optical) Digital Audio Splitter

Technical Specification

Lindy 3 Port TosLink (Optical) Digital Audio Splitter Specification

| | |
|---|--|
| Specifications | Housing Material: Plastic |
| AV Interface: TosLink (Optical) | Net Weight: 0.054kg (0.12lb) |
| Interface Standard: - | Operating Temperature: 0°C - 40°C (32°F - 104°F) |
| Supports Bandwidth: - | Storage Temperature: -10°C - 80°C (14°F - 176°F) |
| Maximum Resolution: - | Humidity: 5-90% RH (non-condensing) |
| HDCP Support: - | Power Requirements: 2.5W |
| Supported Audio: LPCM2.0 / DTS / Dolby Digital | Colour: Black |
| Separate Audio Ports: - | Miscellaneous |
| CEC Support: - | Packaging Type: Carton Box |
| Serial Interface: - | Packaging Dimensions: 133x105x24mm (5.24x4.13x0.94in) |
| Special Features: - | Gross Weight: 0.08kg (0.18lb) |
| Connectors | Warranty (Years): 2 |
| Input: 1 x TosLink (Optical) (Female) | Certified: CE, UKCA, FCC, RoHS, REACH & California Proposition 65 |
| Output: 3 x TosLink (Optical) (Female) | Package Contents |
| Control: - | 3 Port TosLink (Optical) Digital Audio Splitter |
| Power: Mini-USB (Female) | USB Type A to Mini-B Cable, 0.76m |
| Physical Properties | Lindy Manual |
| Dimensions (approx.) WxDxH: 54x60x20mm (2.13x2.36x0.79in) | |