



# Product Data Sheet

## Lindy Standard HDMI Cable, Anthra Line

### Description



From the Lines cable connectivity concept developed by Lindy, Anthra Line HDMI cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line HDMI cables are premium connections that feature triple shielded with 24AWG copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:2:0 8bit are supported. Anthra Line HDMI cables are also capable of transmitting 32 channel audio and Dolby® True HD.

These HDMI 2.0 cables support 10.2Gbps bandwidth capacity in cable lengths from 7.5m up to 20m.

Anthra Line HDMI cables are available in lengths from 0.3m to 20m.

Product	SKU
LINDY STANDARD HDMI CABLE, ANTHRA LINE	LIN-36967

### Key Benefits

- Superior performance and design Standard HDMI 2.0 cable
- Supports UHD resolutions up to 4096x2160@60Hz 4:2:0 8bit
- Robust PVC housing, gold plated connectors and contacts
- Triple shielded cable, corrosion resistant bare copper 24AWG conductors
- HDMI 2.0 compliant, 3D, 4K, 10.2Gbps, HEC, ARC, CEC, Dolby® True HD, DTS-HD Master Audio; 10 year warranty



# Product Data Sheet

## Lindy Standard HDMI Cable, Anthra Line

### Technical Specification

#### Lindy Standard HDMI Cable, Anthra Line Specification

<b>Connectors</b>	<b>Conductor Material:</b> Bare Copper
<b>Connector A:</b> HDMI Type A Male	<b>Conductor Gauge:</b> 24AWG
<b>Connector B:</b> HDMI Type A Male	<b>Shielding:</b> Aluminium Magnesium Alloy 55%
<b>Housing Material:</b> PVC	<b>Specifications</b>
<b>Connector Plating:</b> Gold	<b>Supported Bandwidth:</b> 10.2Gbps
<b>Pin Construction:</b> Phosphor Bronze	<b>Maximum Resolution:</b> 4096x2160@60Hz 4:2:0 8bit
<b>Pin Plating:</b> Gold	<b>Nominal Attenuation:</b> 300kHz-825MHz --- 15dB 825MHz-2.475GHz --- 15 - 29dB 2.475GHz-4.125GHz --- 29 - 44dB 4.125GHz-5.1GHz --- 44 - 48dB
<b>Dimensions (approx.) WxDxH:</b> 21.4x41.44x12.7mm (0.84x1.63x0.5in)	<b>Minimum Bend Radius:</b> 98mm (3.86in)
<b>Cable Construction</b>	<b>Operating Temperature:</b> -20°C - 80°C (-4°F - 176°F)
<b>Length:</b> 0.3m - 20m	<b>Storage Temperature:</b> -25°C - 85°C (-13°F - 185°F)
<b>Standard:</b> HDMI Standard	<b>Miscellaneous</b>
<b>Colour:</b> Black	<b>Packaging Type:</b> Polybag
<b>Type:</b> Round	<b>Warranty (Years):</b> 10
<b>Jacket Diameter:</b> 9.8mm (0.39in)	<b>Certified:</b> RoHS, REACH, UL
<b>Jacket Material:</b> PVC	