



Product Data Sheet

Neutrik NO24FDW-A opticalCON Chassis Connector

Description



Neutrik NO24FDW-A has rear compatibility of opticalCON MTP® 24 chassis fitting with standard MTP® 24 (ELITE male with 20 N springforce) breakout cable allows easy adaptation to fibre standard connectors such as LC, SC, ST. The approved dust shutter ensures high mating cycles and minimal maintenance.

Product	SKU
NEUTRIK NO24FDW-A OPTICALCON CHASSIS CONNECTOR	KF-00-1024

Key Benefits

- Ruggedised and dirt-protected 24-channel fibre optic connection system
- For point-to-point multichannel routing
- Laser protective metal shutter seals dust proof with two-component rubber gasket
- IP65 ingress protection in mated condition with SCDP-*
- Accommodates standard MTP® ELITE MALE with 20 N springforce connectors on the rear for simple installation



Product Data Sheet

Neutrik NO24FDW-A opticalCON Chassis Connector

Technical Specification

Neutrik NO24FDW-A Specification

Gender: Female	Mounting direction: Front mounting
Mechanical	Chassis shape: D
Insertion force: < 45 N	Environmental
Withdrawal force: < 45 N	Flammability: UL 94 V-0
Lifetime: > 2500 mating cycles	Temperature range: -40 °C to +75 °C
Locking force: 1000 N	Optical
Locking device: Push-Pull	Insertion loss: < 0.9 dB / connection