



Product Data Sheet

Neutrik NK02SA-A-3-300 opticalCON DUO ADVANCED
SM/APC 300M GT380RM

Description



The Neutrik opticalCON DUO ADVANCED is an assembled 2 fibres rugged and lightweight mobile field cable, excellent cable retention due to aramid yarn, black PUR outer jacket, available in multi- and single mode (PC or APC), military approved. Ideal for audio and broadcast networks.

The opticalCON DUO cable connector accommodates a standard optical LC-Duplex connector in a ruggedised and durable all-metal housing. It features a spring loaded push-pull locking mechanism and an excellent cable retention utilising aramid yarn. The optical connection is exceptional well protected against dirt and dust by an automatically operated sealing cover. The cable connector comes pre-assembled and is not available as a single component. The cable is available in different lengths and is packed either in a case, on drum or airspool.

Product	SKU
NEUTRIK NK02SA-A-3-300 OPTICALCON DUO ADVANCED SM/APC 300M GT380RM	KQ-37-03300

Key Benefits

- Ruggedised and dirt protected fibre optic connection system
- Waterproof acc. to IP65 safety standard in mated condition
- 2-pole military approved robust and light weight mobile field cable with multi - or single mode fibres
- opticalCON multimode fibre cables offer laser and bend optimised OM3 fibres
- Accommodates standard optical LC-Duplex connectors
- Cable connector features rugged all metal housing and heavy duty cable retention
- Excellent dust and dirt protection due to automatic sealing shutter with silicone gasket
- Reliable Push-Pull locking mechanism
- Easy to clean, no special tools required
- Available in different packaging versions



Product Data Sheet

Neutrik NK02SA-A-3-300 opticalCON DUO ADVANCED
SM/APC 300M GT380RM

Technical Specification

Neutrik NK02SA-A-3-300 Specification

Connection Type: opticalCON	Optical
Gender: male	Insertion loss: < 0.5 dB / connection
Mechanical	Optical connector: LC-Duplex (PC and APC)
Cable retention: > 500 N	Optical wiring: ISO / IEC 11801
Insertion force: < 45 N	Mobile cable
Withdrawal force: < 45 N	Colour: black, matte
Lifetime: > 5000 mating cycles	Core diameter: Singlemode 9 µm, Multimode 50 µm
Locking device: Push-Pull	Cladding diameter: 125 µm
Material	Comment: PUR
Boot: Rubber (EPDM)	Minimal bending radius: 5 cm
Bushing: Zinc diecast (ZnAl4Cu1)	Number of fibres: 2
Insert: Polyamide (PA 6, PBT 30 % GR, PBT 50 % GR)	Cable retention: Aramid yarn
Shell: Zinc diecast (ZnAl4Cu1)	Weight: 23 kg/km
Shell plating: Black chromium	Overall diameter: 5 mm
Strain relief: Polyacetal (POM) (brass)	Environmental
	Temperature range: -40°C to +75 °C

Cable O.D.: 5 mm

