



# Product Data Sheet

## Argosy PRO Patch Fibre Tray

### Description



The Argosy PRO Patch fibre tray has been designed with the broadcast installation in mind. It provides the installer with greater quality and more flexibility when compared with the standard Telco tray.

Constructed from thicker material 1ru tray comes with adjustable rack ears enabling recessing up to 125mm, slam locks providing a more robust repeatable locking solution compared with push rivets, and a broadcast style ident strip.

The sliding tray provides quick and easy access when rack-mounted for ease of installation and maintenance and is suitable for patch cables, splice or pre-term installations, or mixed. Available LC duplex SM, SMAPC, Multimode, custom configuration available upon request.

Accessories: Splice kit/SKU KV-99-005: Optional splice termination kit including – Splice Tray, Pigtailed, Splice shields, M20 Glands.

Available as:

Product	SKU
ARGOSY 1U PRO 12 WAY SC SIMPLEX OM3 FIBRE TRAY	KT-00-9212
ARGOSY 1U PRO 24 WAY SC SIMPLEX OM3 FIBRE TRAY	KT-00-9224
ARGOSY 1U PRO 12 WAY SC SIMPLEX OS2 FIBRE TRAY	KT-00-9312
ARGOSY 1U PRO 24 WAY SC SIMPLEX OS2 FIBRE TRAY	KT-00-9324
ARGOSY 1U PRO 12 WAY LC DUPLEX OM3 FIBRE TRAY	KT-00-9412
ARGOSY 1U PRO 24 WAY LC DUPLEX OM3 FIBRE TRAY	KT-00-9424
ARGOSY 1U PRO 12 WAY LC DUPLEX OS2 FIBRE TRAY	KT-00-9512
ARGOSY 1U PRO 24 WAY LC DUPLEX OS2 FIBRE TRAY	KT-00-9524



# Product Data Sheet

## Argosy PRO Patch Fibre Tray

### Key Benefits

- Large snap fit ident strip
- Adjustable rack ears
- Screw fixed adaptors
- Rear brush strip access for patch cables
- Supplied with adaptors assembled
- Slam locks on sliding tray
- Colour: Black RAL9005
- Cable entry: 2 x cutout for M20 gland & large brush strip

### Technical Specification

#### Argosy PRO Patch Fiber Tray Specification

<b>Height x Width x Depth 1U:</b> 44.4mm x 482mm x 200mm	<b>Cable Entry:</b> 20mm x 2
<b>Net Weight:</b> 3kg	<b>Cable Entry:</b> Brush Strip
<b>Packaged Weight:</b> 3.5kg	<b>Material Thickness:</b> 1.8mm cold rolled steel
<b>Packaged Dimensions:</b> (H) 55mm x (W) 530mm x (D) 260mm	<b>Material Coating:</b> Electrostatic Powder Coating
<b>IP Rating:</b> 20	<b>Colour:</b> Black RAL 9005
<b>Adaptor Type:</b> LC Duplex SMPC/SMAPC/MM	<b>Operating Temperature:</b> -40°C to +60°C
<b>Mounting Adjustment Range:</b> 50mm	<b>Compliant to:</b> This product conforms to the material requirements of RoHS2, REACH/SvHC
<b>Connector Pitch:</b> 15mm	<b>Designed in accordance with:</b> TIA/EIA 568A.C, ISO/IEC 11801, EN50173, IEC 60304, IEC 61754, EN297-1