

Product Data Sheet

Neutrik NE8MCB Cable Connector



The NE8MCB is an RJ45 cable connector carrier for pre-assembled RJ45 plugs consisting of a black chromium shell, fixing disk, chuck, bushing and boot. Packed with two cable protection elements for cable diameters either up to 5 mm or 8 mm. The cable connector carrier does not include a RJ45 plug.

The etherCON cable connector carrier upgrades a conventional RJ45 connector to an extremely robust lockable solution.

Attention! Does not intermate with the CAT6 chassis connectors NE8FDY-C6 and NE8FDY-C6-B.

| Product | SKU |
|--------------------------------|-----------|
| NEUTRIK NE8MCB CABLE CONNECTOR | DB-65-523 |

Key Benefits

- The RJ45 system for harsh and demanding environment
- Cable connector carrier accepts the most common RJ45 plugs (see list at downloads)
- Rugged diecast shell and unique chuck type strain relief
- Protects Ethernet connections in a variety of commercial type applications and is designed to prevent breakage of the fragile

All products and companies referred to herein are trade

components of standard RJ 45 connectors

marks or registered trademarks of their respective companies or mark holders

- Allows assembly of preassembled conventional RJ45 cables
- Accessories include colour coded boots in 9 standard colours

argosycable.com

+44 1844 202101 sales@argosycable.com



Product Data Sheet Neutrik NE8MCB Cable Connector

| | Specification |
|---|-------------------------------------|
| Neutrik NE8MCB Cable Connector Specification | |
| Gender: male | Material |
| Mechanical | Boot: Polyamide (PA 6) |
| Cable O.D.: max. 8 mm 0.315' | Shell: Zinc diecast (ZnAl4Cu1) |
| Insertion force: ≥ 220 N (subject to cable O.D. & material) | Shell plating: Black chromium |
| Withdrawal force: ≤ 20 N | Strain relief: Polyacetal (POM) |
| Lifetime: > 1000 mating cycles | Environmental |
| | Temperature range: -30 °C to +80 °C |