



Product Data Sheet

Argosy BNC HDTV Isolated Bulkhead F-F 12GHZ 750

Description



Typically used for broadcast 12G-SDI / 4K applications such as TV stations and cable channels, the BNC HDTV Isolated Bulkhead enables the transmission of high-resolution uncompressed video signals.

With a nickel-plated brass body, the contact is made from gold-plated Phosphor Bronze, and the washer is nickel-plated phosphor bronze. Can be fitted to recessed or standard panels. Has insulated true 75 Ohm BNC, with a frequency range of DC-12GHz.

Maximum panel thickness is 6.00mm and durability of 500 mating cycles. Temperature resistant between -55 and +85 °C.

Product	SKU
ARGOSY BNC HDTV ISOLATED BULKHEAD F-F 12GHZ 750	BH-65-0005



Product Data Sheet

Argosy BNC HDTV Isolated Bulkhead F-F 12GHZ 750

Technical Specification

Argosy BNC HDTV Isolated Bulkhead Specification

Electrical	Locknut: Brass, Nickel Plated
Dielectric Withstanding: 1500 Volts RMS Maximum	Washer: Phosphor Bronze, Nickel Plated
Impedance: 75 ohms	Mechanical
Interface Frequency: 12 GHz	Contact Gender: Female
Working Voltage: 500 Volts RMS Maximum	Durability: 500 mating cycles
Material	Fixing Method: Panel
Body: Brass, Nickel Plated	Maximum Panel Thickness: 6.00mm
Contact: Phosphor Bronze, Gold Plated	Environmental
Dielectric: PTFE	RoHS Compliant: Yes
Insulator: POM	Temperature Range: -55 to +85°C