



Product Data Sheet

Argosy XLR Panel 1U 1 x 16 Loaded Male Black

Description



The Argosy XLR termination panels are supplied fully loaded with Neutrik 3 pole DLX series connectors and are offered in 3 standard formats, Male, Female and 50/50.

The panel's unique design permits connectors to be loaded from the rear delivering a sleek and aesthetically pleasing front panel. The panels are extremely robust and come supplied with a snap-fit Ident strip, they also feature a large OD on the bar which makes landing cables easier and addresses issues associated with smaller bars.

We also make up custom configurations, to specify your requirement don't hesitate to get in touch with sales on +44 (0)1844 202101 or email sales@argosycable.com.

Product	SKU
ARGOSY XLR PANEL 1U 1 X 16 LOADED MALE BLACK	DP-00-0016



Product Data Sheet

Argosy XLR Panel 1U 1 x 16 Loaded Male Black

Technical Specification

Argosy XLR Panel 1U 1 x 16 Loaded Male Black

Electrical	Wiresize max.: 14 AWG
Capacitance between contacts: ≤ 4 pF	Locking device: Latch lock
Contact resistance: ≤ 5 m Ω (inner)	Chassis shape: D
Dielectric strength: 1,5 kVdc	Lifetime: 1000 mating cycles
Insulation resistance: > 2 G Ω (initial)	Material
Rated current per contact: 16 A	Contact plating: 2 μ m Ag over 2 μ m Ni
Rated voltage: 50 V	Contacts: Bronze (CuSn6)
Mechanical	Insert: Polyamide (PA 6.6 30 % GR)
Insertion force: ≤ 20 N	Shell: Zinc diecast (ZnAl4Cu1)
Withdrawal force: ≤ 20 N	Shell plating: Nickel
Wiresize max.: 2.5 mm ²	Locking element: Stahl Ck67