



Product Data Sheet

Neutrik NAC3FPX-TRUE1 powerCON 16A TRUE1
Outlet Chassis Mount

Description



The “powerCON TRUE1 airtight” is a locking true mains connector for harsh and demanding applications. This innovative product is part of the powerCON-TRUE1 product group and belongs to our premium powerCON-TRUE1 line. With an impressive array of features and a particular focus on protection and performance, the powerCON airtight” is the choice for professionals who require absolute reliability. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

With the powerCON TRUE1 airtight, you can count on a secure connection, even in the most extreme conditions.

The powerCON TRUE1 is a connector series with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.

| Product | SKU |
|---|--------|
| NEUTRIK NAC3FPX-TRUE1 POWERCON 16A TRUE1 OUTLET CHASSIS MOUNT | 105821 |



Product Data Sheet

Neutrik NAC3FPX-TRUE1 powerCON 16A TRUE1
Outlet Chassis Mount

Key Benefits

- Airtightness for production line tests to ensure TRUE OUTDOOR PROTECTION on devices
- Heavy duty sealed power connector for harsh and demanding environment
- Uses high impact UV-resistant materials
- Extremely robust and reliable
- ENEC and VDE certified according to IEC 60320-1 and EN IEC 60320-1
- UL and CSA Certified According to UL 60320-1 and CSA 22.2 No. 60320-1
- IP65, IP66 and IP67 (mated or with closed cap)
- True mains connector with breaking capacity (CBC)
- Easy and reliable twist lock system

Technical Specification

Neutrik NAC3FPX-TRUE1 powerCON 16A TRUE Specification

| Electrical | Material |
|--|---|
| Contact resistance: $\leq 2 \text{ m}\Omega$ | Contact plating: $2 \text{ }\mu\text{m Ag}$ |
| Dielectric strength: 4 kVdc / 2.8 kVac | Locking element: Stainless steel |
| Insulation resistance: $> 1 \text{ G}\Omega$ (after damp and heat test IEC 68-2-30) | Shell: Polyamide (PA 6.6) |
| Number of electrical contacts: 2 + PE | Contacts: Copper Alloy |
| Rating Europe: 16 A / 250 V AC according to EN IEC 60320-1 | Environmental |
| Rating America: 20 A / 250 V AC according to UL 60320-1 20 A / 250 V AC according to CSA C22.2 No. 60320-1 | Flammability: UL 94 V-0 |
| Mechanical | Temperature range: -30°C to $+80^{\circ}\text{C}$ according to IEC 61984 -5°C to $+40^{\circ}\text{C}$ according to IEC 60320-1 |
| Lifetime: > 5000 mating cycles | Protection class: IP 65 / 66 / 67 (mated or with closed caps) |
| Wiresize: 2.5 mm^2 , 12 AWG | UV resistance: F1 rated material withstands UV exposure |